

NEOXPacketLion NX-PBPL-2M

MAXIMISE NETWORK VISIBILITY WITH OUR COST-EFFECTIVE AND INNOVATIVE 100G PACKET BROKER PLATFORM!



Model: NX-PBPL-2M

Network Packet Brokers, also called Data (Network) Monitoring Switches, help you to intelligently manage your passively tapped network data and - through innovative technology - provide the analysis tools with the data packets reliably and in optimised form.

Media type and speed of your network do not matter, as these devices are equipped with QSFP28 connectors and process the data packets without affecting the active line and redistribute them according to your wishes.

By filtering out the data with hardware-based filtering mechanisms before it is routed out, this allows you to evaluate multiple 10G lines with existing 1G analysis tools, for example, while reducing the amount of data for hassle-free and secure analysis. Data that is not of interest is either discarded or sent to other tools for further analysis.



FEATURES

- Flexible port assignment (1:1, N:N, N:1, 1:N)
- Aggregation of 10G, 25G, 40G, 100G, 200G and 400G network ports
- Support for filter rules (MAC, VLAN, IPv4/IPv6, TCP/UDP, DSCP, TCP Flags, MPLS, Ingress, Egress)
- Filtering within a tunnel (GTP, L2TP, MPLS, GRE, VxLAN, etc.)
- Digital Diagnostics Monitoring (DDM)
- Support for user-defined filter rules (UDF)
- Multiple management options (CLI, SSH, SNMP V2/V3, WEB UI, Net CONF and REST API)
- Logging through Syslog and SNMP Traps

HIGHLIGHTS

- Line rate performance without packet loss
- Non-blocking backplane architecture with N+1 redundancy
- Support for L3GRE tunnelling protocol
- Load distribution based on 5-tuple criteria
- Port Splitting (Simplex Mode), Port Labeling
- Support for Jumbo Frames
- MAC Replace
- Radius and TACACS+
- Modular due to QSFP28 interfaces
- 5+1 redundant, hot-swappable fans
- Hot-swappable, load-sharing and redundant AC/DC power supplies

USE CASES

Aggregation of TAP/SPAN traffic in a central location to efficiently provide security and monitoring tools with the data.

Decide for yourself which network traffic you want to forward to which analysis system.

Intelligent load distribution of all data traffic according to the capacity of your connected monitoring systems.


Use the inline options of our PacketLions and simply connect several tools in series to increase your network security (can be combined with intelligent Load Balancing).

Regeneration of data traffic, for example to be able to provide the network data to several security systems in parallel.

Layer 2 matrix switch functionality for any interconnection of network data (many to one, one to many, many to many, any to any), easy media conversion through modular design (QSFP28).

Intelligent filter rules let you sort out the network data to be analysed without loss and without interruption.

Enables you to evaluate 100G/40G/10G network lines using 100G/40G/10G/1G monitoring systems.



SCHNITTSTELLEN

1	System LEDs	5	USB Storage Port	9	PSU 2
2	Port Indicators	6	40G/100G Breakout Mode LEDs	10	Hot-Swappable 5 + 1 Redundant FANS
3	Console Port	7	32x 100G QSFP28 Ports	11	PSU 1
4	Management Port	8	Info Tag	12	Grounding Point

DIMENSIONS (WxHxD) / WEIGHT

43.80 cm x 4.35 cm x 51.50 cm / 10.00 kg

REGULATORY / CE

EMI, CE Mark, FCC Part 15 Subpart B Class A, VCCI Class A, RoHS-6

POWER SUPPLY

AC input range: 90~240 VAC at 50-60 Hz, DC input range: -36 to -72 VDC. Maximum power consumption: 550 W



ITEM NUMBER	QSFP28 PORTS	
NX-PBPL-2M	32x 40G/100G	64x 50G, 128x 10G/25G (via QSFP28)