

Distributed by



NEOX
NETWORKS

sales@neox-networks.com

+49 6103 37 215 910

www.neox-networks.com

Accelerators for Smarter Data Delivery

NT200C01-2x100 200G Performance Solution 2-PORT 100G PCIe GEN3

2 × 100 Gbps PACKET CAPTURE AND ANALYSIS

Use cutting-edge network acceleration technology to add real-time line rate performance to your application. Napatech 2-port 100 Gbps performance solutions provide full packet capture and analysis of network data at 200 Gbps with zero packet loss. The Napatech performance solution will capture all frames, including erroneous frames normally discarded by standard NICs. The Napatech NT200C01-2x100 200G Performance Solution can also be used for in-line application acceleration.

The Napatech performance solution allows you to merge data from ports into a single, time-ordered analysis stream. It supports 1-128 packet streams using intelligent hardware flow distribution to allow your application to scale to higher packet rates with no packet loss. The Napatech performance solution will distribute packets based on flow or on L3/L4 filter criteria.

The 2 × 8 GB DDR3 RAM buffer allows buffering packets on the performance solution to prevent packet loss during peak server loads. Packets are hardware timestamped when they arrive at the network ports, ensuring that the time stamp is always reliable.



FEATURE HIGHLIGHTS

- Scalable pipeline architecture
- Network ports: 2 × CFP4
- Capture of Ethernet traffic: Full 2 × 100 Gbps
- Zero packet loss for all frame sizes
- 2 × 8 GB DDR3 RAM buffer (640 ms at 200 Gbps)
- Typical CPU load: < 5% of one core
- Addressing up to 1 TB application buffer memory
- Packet or segment delivery to application
- Hardware-accelerated:
 - Multi-port packet merge
 - Load distribution across up to 128 CPU cores
 - 1 ns time stamp resolution
 - Frame and protocol information
 - Filtering based on e.g. L3/L4 criteria
 - GTP, IP-in-IP, GRE and NVGRE tunneling support
 - IP fragment handling
 - Slicing at fixed or dynamic offset
 - RMON1 counters, including jumbo frames
- IEEE 1588-2008 PTP and PPS time synchronization
- OS time synchronization
- Easy-to-integrate API
- Linux, Windows, libpcap and WinPcap

NAPATECH-SUPPORTED APPLICATIONS

Napatech accelerators enable OEM vendors to build high-performance network appliances based on standard servers. Examples of applications include:

- Revenue and services optimization
- Quality of experience optimization
- Financial latency measurement
- Customer experience analysis
- Data loss prevention
- Virtualized activity analysis
- Cyber defense
- Fraud detection and compliance management
- Infrastructure management and security
- Network and application performance
- Troubleshooting and compliance

SPECIFICATIONS

GENERAL FEATURES

- Full line-rate processing for all frames from 64 bytes to 10,000 bytes - keep or discard erroneous frames
- IEEE standard: IEEE 802.3 100 Gbps Ethernet support
- Network interface: 2 × CFP4 ports
- Supported CFP4 modules: single-mode LR4
- Data rate: 2 × 100 Gbps
- Typical CPU load: < 5%
- Time formats: PCAP-ns/-μs and UNIX 10 ns
- Time stamp resolution: 1 ns
- Stratum 3 compliant TCXO
- Pluggable options for IEEE 1588-2008 PTP and PPS time synchronization
- PTP slave in IEEE 1588-2008 default and telecom profiles

ACCELERATOR SOFTWARE

- Operating systems: Linux, Windows
- Napatech API for high performance and advanced features
- libpcap
- IEEE 1588-2008 PTP stack
- SDK tools included in source code for debugging and prototyping and as application examples

ACCELERATOR HARDWARE CONFIGURATION

- The NT200C01-2x100 200G Performance Solution is a combination of the following hardware components:
 - 2 × NT100E3-1-PTP accelerators
 - 2 × interconnect cables (different lengths available)
 - 1 × time sync cable (different lengths available)

ACCELERATOR HARDWARE

- Bus type: 2 × 16-lane 8 GT/s PCIe Gen3
- 2 × 8 GB onboard DDR3 RAM
- Flash: Support for two boot images
- Built-in thermal protection
- Physical dimensions: 2 × 3/4-length and full-height PCIe
- Weight excluding CFP4 LR4 modules: 2 × 455 g
- MTBF according to UTE C 80-810: 129,898 hours
- Power consumption including CFP4 LR4 modules: 2 × 75 Watts

ENVIRONMENT FOR NT200C01-2x100 200G Performance Solution

- Operating temperature: 0 °C to 45 °C (32 °F to 113 °F)
- Operating humidity: 20% to 80%

REGULATORY APPROVALS AND COMPLIANCES

- PCI-SIG®, NEBS level 3, CE, CB, RoHS, REACH, cURus (UL), FCC, ICES, VCCI, C-TICK

COMPANY PROFILE

Napatech is the world leader in data delivery solutions for network management and security applications. As data volume and complexity grow, organizations must monitor, compile and analyze all the information flowing through their networks. Our products use patented technology to capture and process data at high speed and high volume with guaranteed performance, enabling real-time visibility. We deliver data faster, more efficiently and on demand for the most advanced enterprise, cloud and government networks. Now and in the future, we enable our customers' applications to be smarter than the networks they need to manage and protect.

Napatech. SMARTER DATA DELIVERY

EUROPE, MIDDLE EAST AND AFRICA

Napatech A/S
Copenhagen, Denmark

Tel. +45 4596 1500
info@napatech.com
www.napatech.com

NORTH AMERICA

Napatech Inc.
Boston, Massachusetts
Los Altos, California
Washington D.C.

Tel. +1 888 318 8288
info@napatech.com
www.napatech.com

APAC

Napatech China/South Asia
Taipei City, Taiwan
Tel. +886 2 28164533 Ext. 319

Napatech Japan K.K.
Tokyo, Japan
Tel. +81 3 5326 3374

ntapacsales@napatech.com
www.napatech.com